

# PROTECTOR 360

## TRANSFORMING DAILY RISK INTO LASTING SECURITY

Turn your hard-earned resilience into sustainable control with the Protector 360, a first-of-its-kind modular shroud compatible with select Protector smart safes. Built into a wall, the shroud provides flexible, through-the-wall functionality, allowing you to separate your operator-facing transactions and your cash-in-transit (CIT) collections.



- Compatible with a range of Protector smart safes
- External shroud built into a wall with an internal rotating barrel
- Superior protection in the closed position
- CIT can be performed in a designated strong room
- Improve CIT efficiency
- International standard of quality and performance
- Protector 360m operates completely manually
- Protector 360a operates remotely via a secure platform for increased protection, with manual capabilities for ultimate control



# PROTECTOR 360

## DIMENSIONS AND WEIGHT

|        |         |
|--------|---------|
| HEIGHT | 2 185mm |
| WIDTH  | 1 070mm |
| DEPTH  | 1 110mm |

## COMPATIBILITY

Compatible with a range of Protector smart safes.

## SECURITY

Superior security in the closed position.

## ACCESSIBILITY

The barrel rotates clockwise allowing access to the smart safe in the open position.

## CIT ACCESS

Accessible from a secure strong/cash room.

## FUNCTIONALITY

Protector 360a - automated  
Protector 350m - manual

## POWER CONSUMPTION

Input Voltage:  
220V - 240V AC  $\pm$  10%, 50Hz ★

Motor Voltage:  
24V DC

Motor Power Supply:  
Battery Driven (Standard Capacity - 2 x 7AH)

Battery Charger:  
2A @27.5V

Current Consumption (mains):  
170mA

Current Consumption (motor at rated load):  
4A / 8A

## WARRANTY

Full maintenance plan over the contract period

Contact us: [deposita.salesadmin@za.g4s.com](mailto:deposita.salesadmin@za.g4s.com) or +27 (0)11 729 3300